

AURVTG003 Remove and install butyl sealed windscreens

Release: 1

AURVTG003 Remove and install butyl sealed windscreens

Modification History

Release	Comment		
Release 1	New unit of competency.		

Application

This unit describes the performance outcomes required to remove and install butyl sealed windscreens. It involves preparing for the task, selecting and using specialist tools and equipment, and removal procedures, applying butyl sealants, installing windscreen according to manufacturer specifications, cleaning and finishing the windscreen, and completing workplace processes and documentation.

It applies to those working in the automotive glazing service and repair industry.

No licensing, legislative, regulatory or certification requirements apply to this unit at the time of publication.

Competency Field

Vehicle Body

Unit Sector

Technical - Glazing

Elements and Performance Criteria

Elements	Performance Criteria		
Elements describe the essential outcomes.	Performance criteria describe the performance needed to demonstrate achievement of the element. Where bold and italicised text is used, further information is detailed in the range of conditions section.		
Prepare for removal and installation of butyl sealed windscreen	1.1 Job requirements are determined from workplace instructions 1.2 Removal and installation information is accessed and interpreted from windscreen manufacturer specifications, workplace procedures, and butyl sealant safety data sheets (SDS) 1.3 Work is planned to minimise waste and use time efficiently		

Approved Page 2 of 4

Elements	Performance Criteria		
Elements describe the essential outcomes.	Performance criteria describe the performance needed to demonstrate achievement of the element. Where bold and italicised text is used, further information is detailed in the range of conditions section.		
	1.4 Vehicle is inspected to ensure there is no prior damage and that all related accessories are operating correctly		
	1.5 Glazing <i>materials</i> and windscreen are selected to meet windscreen specifications and are inspected for quality		
	1.6 Hazards associated with the work are identified and risks are managed		
	1.7 Tools and equipment are selected and checked for serviceability		
	1.8 Vehicle is protected and safely located according to workplace procedures		
Carry out removal and installation activities	2.1 Windscreen is removed according to manufacturer specifications, and <i>safety and environmental requirements</i> , and without causing damage to vehicle or components		
	2.2 Replacement windscreen is installed, sealed and finished according to manufacturer specifications and safety and environmental requirements		
	2.3 Adhesive is cured according to adhesive manufacturer specifications and timelines, as required		
3. Complete work processes	3.1 Final inspection of butyl sealed windscreen is made to ensure work meets workplace expectations, related accessories are operating correctly, and vehicle is presented ready for use		
	3.2 Work area is cleaned, waste and non-recyclable materials are disposed of, and recyclable material is collected and stored		
	3.3 Tools and equipment are checked, reported if faulty, and stored according to workplace procedures		
	3.4 Workplace documentation is processed according to workplace procedures		

Foundation Skills

This section describes those language, literacy, numeracy and employment skills that are essential to performance and are not explicit in the performance criteria.

Skills	Description	
Learning skills to:	locate appropriate sources of information efficiently.	
Writing skills to:	legibly and accurately fill out workplace documentation.	

Approved Page 3 of 4

Skills	Description	
Oral communication skills to:	clarify instructions and proceduresclearly report issues or outcomes.	
Planning and organising skills to:	 select and use appropriate equipment, materials and processes for removing and installing butyl sealed windscreens work within limits of own work role and follow workplace procedures. 	
Technology skills to:	use specialist removal and installation equipment.	

Range of Conditions

This section specifies work environments and conditions that may affect performance. Essential operating conditions that may be present (depending on the work situation, needs of the candidate, accessibility of the item, and local industry and regional contexts) are included. Bold italicised wording, if used in the performance criteria, is detailed below.

<i>Materials</i> must include:	•	butyl sealing materials
	•	solvents and cleaning materials.
Tools and equipment must include:	•	personal protective equipment (PPE)
	•	specialist tools for removing butyl sealed windscreens
	•	hand tools.
Safety and environmental requirements must include:	•	work health and safety (WHS) and occupational health and safety (OHS) requirements, including procedures for:
		selecting and using PPE
		using SDS for butyl sealants
		material handling and storage
	•	environmental requirements, including procedures for trapping, storing and disposing of waste materials and chemicals.

Unit Mapping Information

Equivalent to AURVTG2003 Remove and install butyl sealed windscreens

Links

Companion Volume implementation guides are found in VETNet - https://vetnet.education.gov.au/Pages/TrainingDocs.aspx?q=b4278d82-d487-4070-a8c4-7804 5ec695b1

Approved Page 4 of 4